

# **Upstream and Downstream Passage of American Eels at the Medway Project, Penobscot River, Maine**

**Scott Hall**

---

**PPL Maine, LLC  
Milford, Maine**

**Steve Shepard**

---

**Aquatic Science Associates, Inc.  
Brewer, Maine**


**FERC Fish Passage Workshop, 13 Nov. 2003, Holden, Mass.**

# Medway Project

- ❑ Located in Medway at the mouth of the West Branch, Penobscot River.
- ❑ Fifth dam on river at ~ 60 miles from the mouth.
- ❑ 3.4 MW capacity at 19 ft. of head.
- ❑ 3,450 cfs maximum hydraulic capacity.
- ❑ Uses 2,000 cfs minimum flow from the West Branch Project (Great Lakes Energy).
- ❑ No anadromous fish passage to West Branch.
- ❑ New license granted in 1999.

WEST BRANCH  
PENOBSCOT RIVER

# General Plan View of Medway Dam



# Downstream Bypass

- Bypass is located at the end of the spillway, adjacent to the forebay
- Uses existing gate and stop logs in the top half of the water column
- 15 cfs bypass flow
- Six foot deep weir opening
- Bell mouth weir shape to provide a velocity transition

# Downstream Passage Evaluations

- **Video monitoring conducted in 2002**
- **Video and trapping in 2003**



# Downstream Passage Evaluations

- **Video monitoring conducted in 2002**
  - Reflective background used
  - Infrared lighting and supplemental red light
  - Tested with drogues
  - Real-time recording in six hour blocks
  - Monitored from August through mid-November

# Downstream Passage Evaluations

- **Video monitoring conducted in 2002**
  - Reflective background used.
  - Infrared lighting and supplemental red light.
  - Tested with drogues.
  - Real-time recording in six hour blocks.
  - Monitored from August through mid-November.
  
- **Video and trapping in 2003**
  - Paired video & trapping to assess video effectiveness.
  - An historic weir fishery indicated run timing in August and September.





**Trapping Set-Up  
in 2003**



# Downstream Results Summary

(preliminary)

- **Video monitoring was not effective.**
  - Optimal lighting is very difficult.
  - Turbulence obscures parts of the field of view.
  - Rapid passage is the major problem.

# Downstream Results Summary

(preliminary)

- Video monitoring was not effective.
  - Optimal lighting is very difficult.
  - Turbulence obscures parts of the field of view.
  - Rapid passage is the major problem.
  
- Trapping was an effective monitoring method.
  - Debris and high tailwater caused some problems.
  - Only a few days were trapped in 2003.

# Downstream Results Summary

(preliminary)

- Video monitoring was not effective.
  - Optimal lighting is very difficult.
  - Turbulence obscures parts of the field of view.
  - Rapid passage is the major problem.
  
- Trapping was an effective monitoring method.
  - Debris and high tailwater caused problems.
  - Very few days were trapped in 2003.
  
- Downstream migrants are using the bypass.



Typical eels trapped in 2003





# Upstream Passage Evaluation


## □ Goals

- Determine run timing.
- Document typical size of migrant eels.
- Assess migratory behavior with respect to physical features of the dam.
- Design an upstream fishway and operating plan for the site.

## □ Methods


- Night observations.
- Trapping.

# Upstream Passage Study Area






## 2002 Size Distribution of Migrant Eels



# Seasonal Timing of Medway Eel Migration




# Upstream Passage Summary

- **Nearly all migrant eels were associated with “staging” locations.**
- **Several sizes/ages of eels are active at Medway.**
- **Only the smallest eels are currently able to climb wetted surfaces and pass the dam.**
- **Very small amounts of spill inhibit passage over wetted surfaces.**
- **There were no obvious effects from ambient light.**
- **Migratory activity was not observed until early to mid-June at temperatures above 18 Celsius.**



# Upstream Passage Study Area



# Upstream Passage Summary

- Nearly all migrant eels were associated with “staging” locations.
- **Several sizes/ages of eels are active at Medway.**
- Only the smallest eels are currently able to climb wetted surfaces and pass the dam.
- Very small amounts of spill inhibit passage over wetted surfaces.
- There were no obvious effects from ambient light.
- Migratory activity was not observed until early to mid-June at temperatures above 18 Celsius.

# Upstream Passage Summary

- Nearly all migrant eels were associated with “staging” locations.
- Several sizes/ages of eels are active at Medway.
- **Only the smallest eels are currently able to climb wetted surfaces and pass the dam.**
- **Very small amounts of spill inhibit passage over wetted surfaces.**
- There were no obvious effects from ambient light.
- Migratory activity was not observed until early to mid-June at temperatures above 18 Celsius.



# Upstream Passage Summary

- Nearly all migrant eels were associated with “staging” locations.
- Several sizes/ages of eels are active at Medway.
- Only the smallest eels are currently able to climb wetted surfaces and pass the dam.
- Very small amounts of spill inhibit passage over wetted surfaces.
- There were no obvious effects from ambient light.
- Migratory activity was not observed until early to mid-June at temperatures above 18 Celsius.